

PINNACLE

DISTILLERS YEAST (S)

PRODUCT INFORMATION

DESCRIPTION

PINNACLE DISTILLERS YEAST (S) is an active dry yeast well-suited for use in batch and continuous fermentations of molasses and pure sugars. It has a high tolerance to early residual sugars.

- Has a high cell count ($>1 \times 10^{10}$ cells/g)
- Rehydrates well in direct pitch applications
- Has high ethanol and temperature tolerance
- Has organic acid tolerance
- Can be used in conjunction with nutritional and vitamin supplementations

APPLICATION USE

This yeast product has optimal performance within a pH range of 4.0 to 5.0 but can ferment well in the range of 3.5 to 6.0. Optimal fermentation temperature is dependent on other stresses present (i.e. organic acid, ethanol and pH) but generally ferments well in the range of 33°C to 37°C (92°F to 98°F). Under various process conditions, this yeast can produce high ethanol titres under a broad range of applications and substrate type.

DIRECTIONS FOR USE

Yeast can be added directly to a fermenter at a dose rate of between 0.2 and 0.5 kilograms per 1000 litres (0.44 and 1.1 pounds per 1000 gallons).

PACKAGING

Pinnacle Distillers Yeast (S) is packaged in vacuum-sealed foil bags and shipped in cardboard boxes. Each box contains either 1 x 10kg or 20 x 500g bags (22lb).

STORAGE

Boxes should be stored in a cool, dry place. Product should be used within three years of its production date for best performance. Packages which have lost their vacuum-seal should not be used. Opened packages can be stored cool and used within 3-4 days.

REGULATORY

All yeast conforms to current local regulations.



 **AB Biotek**
PARTNERS IN FERMENTATION™

A business division of AB MAURI

The information presented is based on our research and commercial testing and provides a general assessment of product performance. Nothing contained herein is representative of a warranty or guarantee for which the manufacturer can be held legally responsible.

© 2019 AB MAURI / Date: 1 March 2019 / www.abbiotek.com